

TC-N TYPE RECOMMEND HYDRAULIC OIL
--

[Mineral Oil]

MAKER	NAME
IDEMITSU KOUSAN	DAPHNE SUPER HYDRO A 32 (46)
KYGNUS SEKIYU	UNIT OIL WR 32 (46)
ENEOS	SUPER HYRANDO 32 (46)
COSMO OIL	COSMO HYDRO AW 32 (46)
SHELL	SHELL TELLUS OIL 32 (46)
EXXON MOBIL	MOBIL DTE 10 EXCEL 32(46) or MOBIL DTE 24(25)
BP	ENERGOL SHF-HV 32 (46)
CASTROL	HYSPIN AWH-M 32 (46) or BIOBAR 32 (46)
TOTAL	AZOLLA ZS 32 (46)
CHEVRON	CHEVRON CLARITY HYDRAULIC OIL AW 32 (46)

[Environmental Acceptable Lubricant (EAL)]

MAKER	NAME
CASTROL	BIOBAR 32(46)
PANOLIN	ATLANTIS N32
EXXON MOBIL	MOBIL SHC AWARE H32(46) or MOBIL SHC AWARE HS32(46)
SHELL	NATURELLE HF-E 46
VICKERS OILS	ECOSURE HSE32(46) or ECOSURE EAF32(46)

Note

Regarding the oil viscosity, it should be selected by the supposed condition (ambient temperature and running time).

<The end>