

TC-N/TFN/TFT/NT-F TYPE RECOMMEND LUBRICATION OIL

【 Mineral Oil 】 Gear Oil

MAKER	NAME
IDEMITSU KOUSAN	DAPHNE SUPER GEAR OIL 150 (100)
KYGNUS SEKIYU	GEAR OIL ML 150 (ML 100)
ENEOS	BONNOC M 150 (M 100)
COSMO OIL	COSMO GEAR SE 150 (100)
SHELL	SHELL OMALA OIL 150 (100)
EXXONMOBIL	MOBILGEAR 600 XP 150 (100)
BP	ENERGOL GR-XP 150 (100)
CASTROL	ALPHA SP 150 (100)
TOTAL	CARTER EP 150 (100)
CHEVRON	CHEVRON GEAR COMPOUND EP 150 (100)
LUKOIL	RENOLIN CLP 100

【 Environmental Acceptable Lubricant (EAL) 】 Gear Oil

MAKER	NAME
CASTROL	BIOSTAT 150 (100)
CHEVRON	CLARITY SYNTHETIC EA GEAR OIL 100
EXXONMOBIL	MOBIL SHC AWARE GEAR 150 (100)
GULF OIL MARINE	GULFSEA BD GEAR OIL 150 (100)
KLUBER	KLUBERBIO EG2-150 (100)
LUKOIL	PLANTOGEAR 150S (100S)
SHELL	NATURELLE S4 GEAR FLUID 150 (100)
RSC BIO SOLUTIONS	RSC ENVIRO LOGIC GO 150 (100)
VICKERS OILS	BIOGEAR XP 150 (100)
PANOLIN	MARGEAR 100
TOTAL	BIONEPTAN HT 100

Note

It should be applied the suitable material of seal ring for Environmental Acceptable Lubricants. Please ask NAKASHIMA PROPELLER for combination before use on your thruster.

Regarding the oil viscosity, it should be selected by the supposed condition (ambient temperature and running time).

<The end>