

TCT TYPE THRUSTER RECOMMEND OIL
--

[Mineral Oil]

MAKER	NAME
IDEMITSU KOUSAN	DAPHNE SUPER GEAR OIL 68, 100
KYGNUS SEKIYU	GEAR OIL ML 68, 100
ENEOS	BONNOC TS 68, 100
COSMO OIL LUBRICANTS	COSMO GEAR SE 68, 100
SHELL	SHELL OMALA S2 G 68, 100
EXXONMOBIL	MOBILGEAR 600 XP 68, 100
BP	ENERGOL GR-XP 68, 100
CASTROL	ALPHA SP 68, 100
TOTAL ENERGIES	CARTER EP 68, 100
CHEVRON	CHEVRON GEAR COMPOUND EP 68, 100
GULF MARINE	GULFSEA GEAR OIL 68
LENOL	RENOLIN CLP 68, 100

[Environmental Acceptable Lubricant (EAL)]

MAKER	NAME
CASTROL	BIOTRANS GB 100 (68)
CHEVRON	CLARITY SYNTHETIC EA GEAR OIL 100
EXXONMOBIL	MOBIL SHC AWARE GEAR OIL 100 (68)
GULF MARINE	GULFSEA BD GEAR OIL 100 (68)
KLUBER	KLUBERBIO EG2-100 (68)
LENOL	PLANTOGEAR 100S
SHELL	NATURELLE S4 GEAR FLUID 100 (68)
RSC BIO SOLUTIONS	RSC ENVIRO LOGIC GO 100
VICKERS OILS	BIOGEAR XP 100 (68)
PANOLIN	MARGEAR 100
KAJO	KAJO-BIO-GEAR OIL 100
NOF CORPORATION	MILLUBE ST-100U
TOTAL ENERGIES	BIONEPTAN HT 100

Note

It should be applied the suitable material of seal ring for Environmental Acceptable Lubricants. Please inform us if you apply it.

Regarding the oil viscosity, it should be selected by the supposed condition (ambient temperature and running time). For EAL, the oil viscosity VG100 is as the first recommendation. <THE END>