

TC-N/TFN/TFT/NT-F TYPE RECOMMEND LUBRICATION OIL

【 Mineral Oil 】 Gear Oil

MAKER	NAME
IDEMITSU KOUSAN	DAPHNE SUPER GEAR OIL 150 (100)
KYGNUS SEKIYU	GEAR OIL ML 150 (ML 100)
ENEOS	BONNOC TS 150 (TS 100)
COSMO OIL LUBRICANTS	COSMO GEAR SE 150 (100)
SHELL	SHELL OMALA S2 G 150 (100)
EXXONMOBIL	MOBILGEAR 600 XP 150 (100)
BP	ENERGOL GR-XP 150 (100)
CASTROL	ALPHA SP 150 (100)
TOTAL ENERGIES	CARTER EP 150 (100)
CHEVRON	CHEVRON GEAR COMPOUND EP 150 (100)
LENOL	RENOLIN CLP 100

【 Environmental Acceptable Lubricant (EAL) 】 Gear Oil

MAKER	NAME
CASTROL	BIOTRANS GB 150 (100)
CHEVRON	CLARITY SYNTHETIC EA GEAR OIL 100
EXXONMOBIL	MOBIL SHC AWARE GEAR OIL 150 (100)
GULF MARINE	GULFSEA BD GEAR OIL 150 (100)
KLUBER	KLUBERBIO EG2-150 (100)
LENOL	PLANTOGEAR 150S (100S)
SHELL	NATURELLE S4 GEAR FLUID 150 (100)
RSC BIO SOLUTIONS	RSC ENVIRO LOGIC GO 150 (100)
VICKERS OILS	BIOGEAR XP 150 (100)
PANOLIN	MARGEAR 100
KAJO	KAJO-BIO-GEAR OIL 100
NOF CORPORATION	MILLUBE ST-150U (100U)
TOTAL ENERGIES	BIONEPTAN HT 100

Note

It should be applied the suitable material of seal ring for Environmental Acceptable Lubricants. Please ask NAKASHIMA PROPELLER for combination before use on your thruster.

Regarding the oil viscosity, it should be selected by the supposed condition (ambient temperature and running time). <The end>